

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **GRAFFITIREMOVER GEL STRONG**  
 Alternative number(s) 57697

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Graffiti Remover

#### 1.3 Details of the supplier of the safety data sheet

MAVRO International BV  
 Valeton 15  
 5301 LW Zaltbommel  
 Netherlands

Telephone: +31 418 680 680  
 e-mail: [info@mavro-int.com](mailto:info@mavro-int.com)  
 Website: <https://www.mavro-int.com>

#### 1.4 Emergency telephone number

Emergency information service +31 418 680 680  
 This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

Poison centre					
Country	Name	Postal code/city	Telephone	Telefax	Opening hours
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital		0344 892 0111		Mon - Fri 12:00 AM - 12:00 AM

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.6	flammable liquid	3	Flam. Liq. 3	H226
3.10	acute toxicity (oral)	4	Acute Tox. 4	H302
3.2	skin corrosion/irritation	1	Skin Corr. 1	H314
3.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318

For full text of abbreviations: see SECTION 16.

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

### The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

### Labelling

- Signal word danger

- Pictograms

GHS02, GHS05,  
GHS07



- Hazard statements

H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H314 Causes severe skin burns and eye damage.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P403+P235 Store in a well-ventilated place. Keep cool.

- Hazardous ingredients for labelling potassium hydroxide, 1-butylpyrrolidin-2-one, Hexyl D-glucoside, 2-aminoethanol

## 2.3 Other hazards

of no significance



## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures



#### Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
1-butylpyrrolidin-2-one	CAS No 3470-98-2  EC No 222-437-8	25 - < 50	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319	
ethanol	CAS No 64-17-5  EC No 200-578-6  Index No 603-002-00-5	5 - < 10	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319	

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS No 64742-48-9  EC No 918-481-9	5 - < 10	Asp. Tox. 1 / H304	
potassium hydroxide	CAS No 1310-58-3  EC No 215-181-3  Index No 019-002-00-8	5 - < 10	Acute Tox. 4 / H302 Skin Corr. 1A / H314 Eye Dam. 1 / H318	 
Hexyl D-glucoside	CAS No 54549-24-5  EC No 259-217-6	1 - < 5	Eye Dam. 1 / H318	
2-aminoethanol	CAS No 141-43-5  EC No 205-483-3  Index No 603-030-00-8	1 - < 5	Acute Tox. 4 / H302 Acute Tox. 4 / H312 Acute Tox. 4 / H332 Skin Corr. 1B / H314 STOT SE 3 / H335	 

Name of substance	Specific Conc. Limits	M-Factors	ATE	Exposure route
1-butylpyrrolidin-2-one	-	-	>300 mg/kg	oral
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	-	-	>9.3 mg/l/4h	inhalation: vapour
potassium hydroxide	Skin Corr. 1A; H314: C ≥ 5 % Skin Corr. 1B; H314: 2 % ≤ C < 5 % Skin Irrit. 2; H315: 0.5 % ≤ C < 2 % Eye Dam. 1; H318: C ≥ 2 % Eye Irrit. 2; H319: 0.5 % ≤ C < 2 %	-	333 mg/kg	oral
2-aminoethanol	STOT SE 3; H335: C ≥ 5 %	-	1,089 mg/kg 1,100 mg/kg 11 mg/l/4h	oral dermal inhalation: vapour

For full text of abbreviations: see SECTION 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

**GRAFFITIREMOVER GEL STRONG**

Version number: GHS 1.0

Date of compilation: 2023-01-26

**Following eye contact**

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

**Following ingestion**

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms and effects are not known to date.

**4.3 Indication of any immediate medical attention and special treatment needed**

none

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media**

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO<sub>2</sub>)

**Unsuitable extinguishing media**

Water jet

**5.2 Special hazards arising from the substance or mixture**

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

**Hazardous combustion products**

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Remove persons to safety.

**For emergency responders**

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

**6.2 Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

**6.3 Methods and material for containment and cleaning up****Advice on how to contain a spill**

Covering of drains

**Advice on how to clean up a spill**

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

**GRAFFITIREMOVER GEL STRONG**

Version number: GHS 1.0

Date of compilation: 2023-01-26

**Appropriate containment techniques**

Neutralisation techniques. Use of adsorbent materials.

**Other information relating to spills and releases**

Place in appropriate containers for disposal. Ventilate affected area.

**6.4 Reference to other sections**

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling****Recommendations****- Measures to prevent fire as well as aerosol and dust generation**

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Never add water to this product. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

**- Specific notes/details**

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

**- Handling of incompatible substances or mixtures**

Do not mix with acids.

**Advice on general occupational hygiene**

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feed-stuffs.

**7.2 Conditions for safe storage, including any incompatibilities****Managing of associated risks****- Explosive atmospheres**

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

**- Flammability hazards**

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

**Control of effects****Protect against external exposure, such as**

frost

**- Ventilation requirements**

Use local and general ventilation. Ground/bond container and receiving equipment.

**- Packaging compatibilities**

Only packagings which are approved (e.g. acc. to ADR) may be used.

**7.3 Specific end use(s)**

See section 16 for a general overview.

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
EU	2-aminoethanol	141-43-5	IOELV	1	2.5	3	7.6			H	2006/15/EC
GB	potassium hydroxide	1310-58-3	WEL				2				EH40/2005
GB	2-aminoethanol	141-43-5	WEL	1	2.5	3	7.6				EH40/2005
GB	ethanol	64-17-5	WEL	1,000	1,920						EH40/2005

#### Notation

#### Ceiling-C

#### H

#### STEL

#### TWA

ceiling value is a limit value above which exposure should not occur

absorbed through the skin

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
1-butylpyrrolidin-2-one	3470-98-2	DNEL	24.1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
1-butylpyrrolidin-2-one	3470-98-2	DNEL	10 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
potassium hydroxide	1310-58-3	DNEL	1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
Hexyl D-glucoside	54549-24-5	DNEL	420 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Hexyl D-glucoside	54549-24-5	DNEL	595,000 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-aminoethanol	141-43-5	DNEL	1 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
2-aminoethanol	141-43-5	DNEL	0.51 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
2-aminoethanol	141-43-5	DNEL	3 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
1-butylpyrrolidin-2-one	3470-98-2	PNEC	4 mg/l	aquatic organisms	freshwater	short-term (single instance)
1-butylpyrrolidin-2-one	3470-98-2	PNEC	0.4 mg/l	aquatic organisms	marine water	short-term (single instance)
1-butylpyrrolidin-2-one	3470-98-2	PNEC	30.62 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
1-butylpyrrolidin-2-one	3470-98-2	PNEC	20.17 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
1-butylpyrrolidin-2-one	3470-98-2	PNEC	2.017 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
1-butylpyrrolidin-2-one	3470-98-2	PNEC	1.68 mg/kg	terrestrial organisms	soil	short-term (single instance)
Hexyl D-glucoside	54549-24-5	PNEC	0.176 mg/l	aquatic organisms	freshwater	short-term (single instance)
Hexyl D-glucoside	54549-24-5	PNEC	0.018 mg/l	aquatic organisms	marine water	short-term (single instance)
Hexyl D-glucoside	54549-24-5	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Hexyl D-glucoside	54549-24-5	PNEC	0.722 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Hexyl D-glucoside	54549-24-5	PNEC	0.072 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Hexyl D-glucoside	54549-24-5	PNEC	0.654 mg/kg	terrestrial organisms	soil	short-term (single instance)
2-aminoethanol	141-43-5	PNEC	0.07 mg/l	aquatic organisms	freshwater	short-term (single instance)
2-aminoethanol	141-43-5	PNEC	0.007 mg/l	aquatic organisms	marine water	short-term (single instance)
2-aminoethanol	141-43-5	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-aminoethanol	141-43-5	PNEC	0.357 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2-aminoethanol	141-43-5	PNEC	0.036 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
2-aminoethanol	141-43-5	PNEC	1.29 mg/kg	terrestrial organisms	soil	short-term (single instance)

### 8.2 Exposure controls

#### Appropriate engineering controls

General ventilation.

#### Individual protection measures (personal protective equipment)

##### Eye/face protection

Wear eye/face protection.

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

### Skin protection

#### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374.

#### - Type of material

NBR: acrylonitrile-butadiene rubber, IIR: isobutene-isoprene (butyl) rubber, Nitrile

#### - Material thickness

>0,4mm

#### - Breakthrough times of the glove material

>480 minutes (permeation: level 6)

#### - Other protection measures

Wash hands thoroughly after handling.

### Body protection

Protective clothing against liquid chemicals.

### Respiratory protection

[In case of inadequate ventilation] wear respiratory protection. Type: AX-P2 (gas filters and combined filters against low-boiling point organic compounds and particles, colour code: Brown/White).

### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	brown
Odour	Solvent
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	200 °C
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	0.6 vol% - 13.5 vol%
Flash point	46 °C
Auto-ignition temperature	>200 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	14 (base)
Kinematic viscosity	not determined



## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

### Solubility(ies)

Water solubility	miscible in any proportion
------------------	----------------------------

### Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapour pressure	not determined
-----------------	----------------

### Density and/or relative density

Density	0.99 g/cm <sup>3</sup>
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

## 9.2 Other information

Information with regard to physical hazard classes	there is no additional information
--	------------------------------------

### Other safety characteristics

Miscibility	Completely miscible with water.
-------------	---------------------------------

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### 10.5 Incompatible materials

Acids, Oxidisers

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

Release of flammable materials with:

Light metals (due to the release of hydrogen in an acid/alkaline medium)

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to GHS

##### Acute toxicity

Harmful if swallowed.

##### - Acute toxicity estimate (ATE)

Oral 810.5 mg/kg

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
1-butylpyrrolidin-2-one	3470-98-2	oral	>300 mg/kg
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	64742-48-9	inhalation: vapour	>9.3 mg/l/4h
potassium hydroxide	1310-58-3	oral	333 mg/kg
2-aminoethanol	141-43-5	oral	1,089 mg/kg
2-aminoethanol	141-43-5	dermal	1,100 mg/kg
2-aminoethanol	141-43-5	inhalation: vapour	11 mg/l/4h

##### Skin corrosion/irritation

Causes severe skin burns and eye damage.

##### Serious eye damage/eye irritation

Causes serious eye damage.

##### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

##### Carcinogenicity

Shall not be classified as carcinogenic.

##### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

##### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

**Specific target organ toxicity - repeated exposure**

Shall not be classified as a specific target organ toxicant (repeated exposure).

**Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

**11.2 Information on other hazards**

There is no additional information.

**SECTION 12: Ecological information****12.1 Toxicity**

Shall not be classified as hazardous to the aquatic environment.

**12.2 Persistence and degradability**

Data are not available.

**12.3 Bioaccumulative potential**

Data are not available.

**12.4 Mobility in soil**

Data are not available.

**12.5 Results of PBT and vPvB assessment**

Data are not available.

**12.6 Endocrine disrupting properties**

None of the ingredients are listed.

**12.7 Other adverse effects**

Data are not available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Waste treatment-relevant information**

Solvent reclamation/regeneration. Regeneration of bases.

**Sewage disposal-relevant information**

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

**Waste treatment of containers/packagings**

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

**Remarks**

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR/RID	UN 1814
IMDG-Code	UN 1814
ICAO-TI	UN 1814

#### 14.2 UN proper shipping name

ADR/RID	POTASSIUM HYDROXIDE SOLUTION
IMDG-Code	POTASSIUM HYDROXIDE SOLUTION
ICAO-TI	Potassium hydroxide solution

#### 14.3 Transport hazard class(es)

ADR/RID	8
IMDG-Code	8
ICAO-TI	8

#### 14.4 Packing group

ADR/RID	II
IMDG-Code	II
ICAO-TI	II

#### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

#### 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

#### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

#### Information for each of the UN Model Regulations

#### **Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) - Additional information**

Classification code	C5
Danger label(s)	8



Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	E
Hazard identification No	80
Emergency Action Code	2R

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

### Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) - Additional information

Classification code C5  
 Danger label(s) 8



Excepted quantities (EQ) E2  
 Limited quantities (LQ) 1 L  
 Transport category (TC) 2  
 Hazard identification No 80

### International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant -  
 Danger label(s) 8



Special provisions (SP) -  
 Excepted quantities (EQ) E2  
 Limited quantities (LQ) 1 L  
 EmS F-A, S-B  
 Stowage category A  
 Segregation group 18 - Alkalis

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 8



Special provisions (SP) A3  
 Excepted quantities (EQ) E2  
 Limited quantities (LQ) 0,5 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

#### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

#### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

### Water Framework Directive (WFD)

List of pollutants (WFD)			
Name of substance	CAS No	Listed in	Remarks
potassium hydroxide		a)	

#### Legend

A) Indicative list of the main pollutants

### Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

### National regulations (GB)

#### Restrictions according to GB REACH, Annex 17

none of the ingredients are listed

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
GRAFFITIREMOVER GEL STRONG	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		3

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
Acute Tox.	Acute toxicity
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits ( <a href="http://www.nationalarchives.gov.uk/doc/open-government-licence/">http://www.nationalarchives.gov.uk/doc/open-government-licence/</a> )
EINECS	European Inventory of Existing Commercial Chemical Substances

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

Abbr.	Descriptions of used abbreviations
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

### Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

## GRAFFITIREMOVER GEL STRONG

Version number: GHS 1.0

Date of compilation: 2023-01-26

**Classification procedure**

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**List of relevant phrases (code and full text as stated in section 2 and 3)**

Code	Text
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.