

BUTYLACETATE

Powerful and biodegradable solvent suitable for cleaning paint and coating residues, tools and equipment.



Product description

Butylacetate is a powerful and very effective solvent with a strong degreasing and dissolving effect.

is excellent for removing overspray, dissolving latex paints and cleaning tools and equipment.

Butylacetate is used to remove Nitocoat residues from used tools, such as (HVLP) spray equipment.

Use

Butylacetate is safe for practically all materials. Be careful on painted surfaces.

Characteristics

- Quickly and effectively removes grease residues
- Safe for practically all surfaces
- It is not a petroleum product
- Suitable as a cleaner for application tools
- Biodegradable

Technical data

| | |
|------------------|----------------|
| Odour: | Fruity |
| Colour: | Colourless |
| Specific weight: | 0,88 kg/L |
| pH: | Not applicable |
| Flashpoint: | 24°C |
| Boiling point: | 126°C |

Application conditions

Butylacetate can be used in all weather conditions. Proper ventilation is necessary when used indoors.

Instructions

1. Apply Butylacetate undiluted with a clean cloth or sponge.
2. Scrubbing the surface with a white pad or scouring pad will speed up the process. Paint residues can be scratched away with a putty knife or scraper.
3. Wipe the surface and dry with a clean cloth.
4. Repeat the process if necessary.

Packaging

1, 5, 10 and 25 L

Consumption

Consumption is 10-20 m² per Liter

Practical information

- Be careful with painted surfaces. Always test on the surface before application.
- Do not mix with other products.
- Butylacetate evaporates quickly and leaves no residue.

Storage

Can be kept for at least 24 months in original unopened packaging.

Store in a cool, frost-free place.

Health and safety

Wear suitable protective gloves and safety goggles and use a respirator with a brown filter cartridge (organic vapors) when used in a poorly ventilated area. If in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680
E. info@mavro-int.com
W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: January 2021

All previous editions become invalid upon this publication

Product code: 57807