

FACADECLEAN ALKALINE

Powerful alkaline facade-cleaner for extremely soiled,
acid-sensitive mineral surfaces



Product description

Facadeclean Alkaline is an alkaline facade-cleaner based on potassium hydroxide. Facadeclean Alkaline has an active effect and is applicable on heavily soiled mineral surfaces. Facadeclean Alkaline effectively removes common facade contaminations.

Use

Facadeclean Alkaline is suitable for cleaning acid-sensitive mineral surfaces such as limestone, sandstone, concrete, polished and unpolished marble and masonry.

Characteristics

- Biodegradable
- Excellent cleaning properties on heavy soiled surfaces
- Safe for calcareous surfaces

Technical data

Odour: Odourless
Colour: Transparent
Specific weight: 1,20 kg/L
pH: ~ 14
Contains: Potassium Hydroxide

Application conditions

Facadeclean Alkaline can be used in all dry weather conditions.

Instructions

1. Apply Facadeclean Alkaline undiluted with a low pressure spray or brush.
2. Let the product sit 10 to 60 minutes on the surface. Keep the surface saturated during treatment.
3. Rinse and clean the surface with a high pressure spray. Use between 50 and 200 bar of pressure, this depends on the surface. Use cold or warm water with a maximum temperature of 50 °C.
4. Repeat the procedure if necessary.

Packaging

1, 10 and 25 L

Consumption

Consumption is 5-15 m²/L. Consumption greatly depends on the nature and degree of soiling and porosity of the surface.

Practical information

- Do not mix with other products. Be especially careful with acidic products.
- Low temperature may lower the efficacy of the product, adjust the treatment time accordingly.
- Do not apply on hot surfaces or in direct sunlight.
- Do not allow the product to dry on the surface.

Storage

Can be kept for at least 24 months in original unopened packaging.
Store in a ventilated, cool and frost-free place.

Health and safety

Causes severe burns and eye damage. Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. If in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680
E. info@mavro-int.com
W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2020

All previous editions become invalid upon this publication

Product code: 57641