

FACADECLEAN EXTRA STRONG

Powerfully acidic facade cleaner for extremely dirty, acidsensitive substrates

Product description

Facadeclean Extra Strong is a very concentrated acid facadecleaner based on hydrofluoric acid (HF) and phosphoric acid. Facadeclean Extra Strong has a very powerful efficiency and is applicable on the most extreme soiled mineral surfaces. Facadeclean Extra Strong Effectively Removes Common facade contaminations and scale build up.

Use

Facadeclean Extra Strong is suitable for most mineral surfaces including concrete, masonry and pavers.

Facadeclean Extra Strong is not suitable for glass or calcareous stones such as marble and travertine.

Characteristics

- Very powerful
- Highly concentrated
- Fast-acting
- Very thorough and efficient cleaning that removes all types of facade contaminations and scale build up

Technical data

Odour: Strong acid
Colour: Transparent
Specific weight: 1,12 kg/L
pH: <1

Contains: Hydrofluoric acid (HF) and phosphoric acid

Application conditions

Facadeclean Extra Strong can be used in all dry weather conditions.

Instructions

- Before applying Facadeclean Extra Strong make sure to cover all surfaces that will not be treated with plastic, such as paintwork, paving, metals, glass and cladding.
- Dilute Facadeclean Extra Strong maximum 1:4 with water.
 Before use make sure to wet the surface with water.
- 3. Apply Facadeclean Extra Strong with a soft brush.
- Work from bottom to top to avoid leak marks and staining.
- Let the product sit 1 to 15 minutes on the surface. Keep the surface saturated during treatment and make sure the product does not dry out.
- 6. Rinse and clean the surface with high pressure spray and warm water. Use between 50 and 200 bar of pressure, this depends on the surface. Use cold or warm water with a maximum temperature of 50°C.
- 7. Repeat the procedure if necessary.

Packaging

10 L

Consumption

Consumption is 5-15 m2/L. Consumption greatly depends on the nature and degree of contamination and porosity of the surface.

Practical information

 Do not mix with other products. Be especially careful with alkaline products.



- Low temperature may lower the efficacy of the product, adjust the treatment time accordingly.
- Do not apply on hot surfaces or in direct sunlight.
- Do not allow the product to dry on the surface.

Storage

Can be kept for at least 24 months in original unopened packaging. Store in a ventilated, cool and frost-free place.

Health and safety

Causes severe burns and eye damage. Do not breathe vapor, mist or spray. Avoid skin and eye contact, wear suitable gloves, protective clothing, face protection and safety glasses. Facadeclean Extra Strong contains hydrofluoric acid, contact a doctor immediately after contact. After skin contact: Immediately flush the skin with plenty of lukewarm running water, for a maximum of 5 minutes. Then apply a thick layer of calcium gluconate gel to the affected skin. After 2 minutes, rinse off the coat and apply again. Repeat every 2 minutes until the pain subsides or until medical attention is available. Always consult the safety data sheet or our R&D department before use.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel

T. +31 418 680 680

E. info@mavro-int.com

W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2023

All previous editions become invalid upon this publication

Product code: 57646

WORK