

UNICLEAN HIGH ALKALINE

Strong alkaline detergent for cleaning heavily soiled surfaces



Product description

Uniclean High Alkaline is a powerful alkaline detergent for heavy grease deposits, soot, nicotine and other extreme pollution.
Uniclean High Alkaline contains very strong emulsifiers and surfactants and removes very stubborn pollution.
Uniclean High Alkaline is more environmentally friendly than other strong detergents and is 100% biodegradable.

Use

Uniclean High Alkaline can be applied to natural stone and brick, concrete, tiles, 2-component coatings and various plastics (PVC, PC, PMMA). Do not apply on alkali-sensitive surfaces such as linoleum, alkyd paints and varnishes.

Characteristics

- Highly alkaline
 - > 100% biodegradable
- Can be used on all alkali-resistant surfaces
- Less harmful to the environment than other strong detergents
- Extremely powerful dissolving power

Technical data

Odour: Citrus
Colour: Brown
Specific weight: 1,25 kg/L
pH: 14 (alkaline)

Contains: Potassiumhydroxide, Alcohols, C9-C11,

Ethoxylated, Hexyl D-glucoside, Tetrasodium N,N bis(carboxylatomethyl)-L-glutamate

Application conditions

Uniclean High Alkaline can be applied in all weather conditions, when used indoor ensure proper ventilation.

Instructions

- Depending on the pollution, dilute Uniclean High Alkaline with water or use concentrated.
- 2. Apply Uniclean High Alkaline with a microfiber cloth or brush.
- Let the product work on the surface for a couple of minutes.
 Scrubbing the surface with a white pad or powersponge speeds up the process.
- Rinse the surface with water and/or wipe with a moist microfiber cloth.
- Repeat the procedure if necessary.

Packaging

5 and 10 L

Consumption

Consumption is strongly dependent on degree of soiling and dilution used.

Practical information

- Do not mix with other products, be careful with acidic products.
- Do not use on alkali-sensitive surfaces.
- Avoid inhalation of aerosols.

Storage

Can be stored for at least 24 months in original unopened packaging. Store in a cool, frost-free place.

Health and safety

Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. Avoid inhalation of aerosols and mist. When in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel

T. +31 418 680 680 E. info@mavro-int.com W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: October 2024

All previous editions become invalid upon this publication

Product code: 57639