

UNICLEAN LOW FOAMING

Highly efficient low foaming alkaline detergent for all types of pollution



Product description

Uniclean Low Foaming is a very efficient low foaming detergent for grease deposits, soot, nicotine and other types of pollution. Uniclean Low Foaming is very useful as an all-purpose cleaner in professional and industrial environments. Replaces petroleum cleaners and ammonia cleaners.

Uniclean Low Foaming has a low foaming effect and therefore suitable for use in (scrubbing) machines.

Uniclean Low Foaming is environmentally friendly and 100% biodegradable.

Use

Uniclean Low Foaming can be used on almost all materials.

Characteristics

- Strong alkaline
- Gentle on the surface
- 100% biodegradable
- Effective in cold water
- Suitable as a paint cleaner for paintwork
- Replaces petroleum and ammonia cleaners
- Very suitable for scrubbing machines

Technical data

Odour:	Light yellow
Colour:	Citrus
Specific weight:	1,06 kg/L
pH:	13 (alkaline)
Contains:	Capryleth-9 carboxylic acid, potassiumhydroxide

Application conditions

Uniclean Low Foaming can be applied in all weather conditions, when used indoors ensure proper ventilation.

Instructions

1. Depending on the pollution, dilute Uniclean Low Foaming with water or use concentrated (dilute up to 1:30).
2. Apply Uniclean Low Foaming with a low pressure sprayer, microfiber cloth or brush.
3. Let the product work on the surface for a couple of minutes. Scrubbing the surface with a white pad or power sponge speeds up the process.
4. Rinse the surface with water and/or wipe with a damp microfiber cloth.
5. Repeat the procedure if necessary.

Packaging

1, 5 and 10 L

Consumption

Consumption is strongly dependent on degree of fouling and dilution used.

Practical information

- Do not mix with other products, be careful with acidic products.

Storage

Can be stored for at least 24 months in original unopened packaging. Store in a cool, frost-free place.

Health and safety

Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. When in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680

E. info@mavro-int.com
W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: January 2021

All previous editions become invalid upon this publication

Product code: 54110