

FLOORGUARD FLUOR

High-quality impregnating agent for water-, grease- and dirt-repellent mineral surfaces



Product description

Floorguard Fluor is a waterborne impregnating agent based on fluoropolymers. Floorguard Fluor makes the surface long-term water repellent as well as giving it strong grease- and dirt-repellent properties. Floorguard Fluor penetrates deep in the surface and gives a transparent and long-term effect.

Use

Floorguard Fluor is specially developed for application on light porous mineral surfaces such as tiles, natural stone, concrete and pavers. Examples are shopping centers, kitchens, terraces, squares and busy streets.

Characteristics

- Invisible and transparent
- Durable and abrasion resistant
- Suitable for many mineral surfaces
- UV-light resistant
- Safe and easy to use
- Simple application

Technical data

Odour: Mild characteristic
Colour: White emulsion
Specific weight: 1,0 kg/L
pH: ~6
Flashpoint: >100°C

Dust-free: 10 - 20 minutes
Dry: after approx. 1 - 1.5 hours
Fully cured: after 6 - 8 hours

Application conditions

Ambient temperature: maximum 30°C, minimum 10°C
Substrate temperature: maximum 30°C, minimum 10°C
Relative humidity: maximum 85%

Instructions

1. Ensure that the surface is clean, dry and dust-free before application.
2. Apply Floorguard Fluor undiluted with a low pressure spray or a shorthaired roller.
3. Apply two layers wet-on-wet to ensure complete saturation of the surface.
4. Remove excess material with a lint-free cloth.

Packaging

5 and 10 L

Consumption

Consumption is 2-7 m²/L. Consumption is influenced by the absorbance and porosity of the surface.

Practical information

- Do not dilute or mix with other products
- Remove excess material
- Can give a slight colour deepening effect on certain surfaces
- Clean future contamination with Uniclean

Storage

Can be kept for at least 12 months in original unopened packaging. Store in a cool, frost-free place.

Health and safety

Floorguard Fluor is not classified. If in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680
E. info@mavro-int.com
W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2020

All previous editions become invalid upon this publication

Product code: 57644