

FLOORGUARD SEALER

Waterborne sealer for all water resistant floors



Product description

Floorguard Sealer is an effective waterborne sealer for making floors dust-free and abrasion resistant.

Floorguard Sealer ensures the optimal maintenance of porous floors due to a pore filling effect and excellent adhesion.

Floorguard Sealer is also suitable as a primer for polymer floor-wax such as Floorguard Polycryl.

Use

Floorguard Sealer is suitable for all sorts of water resistant floors such as linoleum, vinyl, PVC, concrete and tiles.

Characteristics

- Excellent adhesion
- Very abrasion resistant
- User-friendly
- Waterborne
- Easy application

Technical data

Odour: Odourless
Colour: White/ beige emulsion
Specific weight: 1,0 kg/L
pH: ~ 7

Dust-free: approx. 1 hour
Dry: approx. 3 hours
Recoat-able: approx. 10 hours

Application conditions

Ambient temperature: minimum 10°C
Substrate temperature: minimum 10°C
Relative humidity: maximum 80%

Instructions

1. Ensure that the surface is completely clean, dry and dust-free.
2. Apply Floorguard Sealer undiluted on the surface and distribute the product with a roller, squeegee, low pressure spray evenly with a roller, squeegee or low pressure spray.
3. An extra later might be necessary on extreme absorbent surfaces.
4. Remove any excess material immediately with a lint-free cloth.

Packaging

5 L

Consumption

Consumption is 1-14 m²/L. Consumption is influenced by the absorbance and porosity of the surface.

Practical information

- Do not dilute or mix with other products
- Remove excess material immediately
- Not suitable for rubber floors

Storage

Can be kept for at least 12 months in original unopened packaging.

Store in a cool, frost-free place.

Health and safety

Floorguard Sealer is not classified. If in doubt, always consult the safety data sheet or our R&D department.

Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680
E. info@mavro-int.com
W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2020

All previous editions become invalid upon this publication

Product code: 54130