

GRAFFITIGUARD PERMANENT HD PRIMER

Adhesion promoting primer for Graffitiguard Permanent HD



Product description

Graffitiguard Permanent HD Primer is an easy to apply, transparent, 1-component adhesion primer for smooth surfaces. Graffitiguard Permanent HD Primer cures at room temperature to form a strong adhesion layer between the substrate and Graffitiguard Permanent HD.

Use

Graffitiguard Permanent HD Primer can be used on all smooth and non-porous materials such as metals, plastics, paint and smooth composite materials.

Characteristics

- Very low consumption rate
- 1-component and easy to process
- Significantly improves adhesion and durability of silicone based coatings
- Quick drying

Technical data

Odour: White spirit
Colour: Transparent
Specific weight: 0,80 kg/L
Flash-point: 63°C

Application conditions

Ambient temperature: maximum 35°C, minimum 8°C
Substrate temperature: maximum 35°C, minimum 8°C
Relative humidity: maximum 80% and 3°C above dewpoint

Instructions

1. Clean the surface to be treated and remove graffiti and other contamination such as soot, wax, oil, paint residues, etc.
2. Make sure that the surface is completely intact, dry and free of dust.
3. Apply Graffitiguard Permanent HD Primer in a very thin layer using a microfiber sponge. Best results are achieved with a layer thickness between 1 and 10 microns.
4. Allow primer to cure at ambient temperature for 1 – 2 hours before applying Graffitiguard Permanent HD. Application of Graffitiguard Permanent HD should take place within 5 hours of application of the primer.

Drying

Dried: 2 – 4 hours

Packaging

100 mL, 1 and 5 liters

Consumption

Consumption is 60-80 m² per liter

Practical information

- Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition.
- Always perform a test piece prior to large scale application.

Storage

Can be kept for at least 12 months in original unopened packaging.

Store in a well-ventilated, cool and frost-free place.

Health and safety

Flammable liquid and vapor. Avoid inhalation of aerosols. Avoid skin and eye contact, wear suitable gloves, protective clothing and safety glasses. If in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680

E. info@mavro-int.com

W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2021

All previous editions become invalid upon this publication

Product code: 00000