

MAVROSEAL FLUOR

High-quality impregnating agent for making mineral surfaces water-, grease- and dirt-repellent



Product description

Mavroseal Fluor is a waterborne impregnating agent based on fluoropolymers.

Mavroseal Fluor not only makes the surface long-term water-repellent, but also has strong grease- and dirt-repellent properties.

Mavroseal Fluor penetrates deep in to the surface resulting in an invisible, effective and long-term effect.

Use

Mavroseal Fluor has been specially developed for application on lightly porous mineral surfaces such as tiles, natural stone, concrete and pavers.

Mavroseal Fluor is widely applied on areas that are prone to stain due to grease- and food residues. Examples are shopping malls, kitchens, terraces, stairwells, squares and busy streets.

Characteristics

- Invisible, transparent
- Durable and wear resistant
- Suitable for many types of mineral surfaces
- UV-resistant
- Safe and easy to use
- Straightforward application

Technical data

Odour:	Characteristically mild
Colour:	White emulsion
Specific weight:	~1,0 kg/L
pH:	~ 7,6
Flashpoint:	>100°C

Dust-free:	10 - 20 minutes
Dry:	after approx. 1 - 1.5 hours
Fully cured:	after 6 - 8 hours

Application conditions

Ambient temperature:	maximum 30°C, minimum 10°C
Substrate temperature:	maximum 30°C, minimum 10°C
Relative humidity:	max.85%

Instructions

1. Ensure that the surface is clean, dry and dust-free.
2. Apply Mavroseal Fluor undiluted with a low pressure spray or short-haired roller.
3. Apply a second layer wet-on-wet to ensure complete saturation of the surface.
4. Remove excess material with a lint-free cloth.

Packaging

5 and 10 L

Consumption

Consumption is 2-7 m²/L, this depends on the absorbency and porosity of the surface.

Practical information

- Do not mix or dilute with other products.
- Remove excess material immediately.
- Can give a slight colour deepening effect on the surface.
- Clean future pollution with Uniclean

Storage

Can be kept for at least 12 months in original unopened packaging.

Store in a cool, frost-free place.

Health and safety

Mavroseal Fluor is not classified. If in doubt, always consult the safety data sheet or our R&D department.

Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel

T. +31 418 680 680

E. info@mavro-int.com

W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2020

All previous editions become invalid upon this publication

Product code: TBD