

MAVROSEAL WB

High-quality waterborne impregnating agent based on silane/siloxane with excellent durability and water repellent effect.



Product description

Mavroseal WB is a high-quality waterborne impregnating agent based on silane/siloxane.

Mavroseal WB penetrates deep within the surface and leaves a long-lasting water repellent effect.

Mavroseal WB does not seal the surface and is therefore 100% vapor permeable.

Mavroseal WB has excellent UV- and alkali-resistance.

Use

Mavroseal WB is suitable for the impregnation of both old and new mineral surfaces such as brick, mineral stucco, concrete, sand-lime brick and natural stone.

Characteristics

- Highly water resistant
- 100% vapor permeable
- High penetration ability
- Reduces dirt-adhesion
- Prevents white deposit
- Solvent-free

Technical data

Odour:	Characteristically mild
Colour:	White
Specific weight:	~1,0 kg/L
pH:	~ 7
Contains:	Silanes/Siloxanes

Application conditions

Ambient temperature:	maximum 30°C, minimum 10°C
Substrate temperature:	maximum 30°C, minimum 10°C
Relative humidity:	max.95% and 3°C above dewpoint During application and drying.

Instructions

1. Clean facades with a pressure washer. For extremely polluted surfaces use a suitable façade-cleaner such as Facadeclean. Remove algae, moss and mold with Algen Remover.
2. Cover surfaces that will not be treated such as glass, window frames, pavement and plants with foil.
3. Ensure that the surface is completely dry.
4. Apply Mavroseal WB undiluted with a low pressure spray, a roller or with the flow method. Work carefully from bottom to top and apply an eventual second layer wet-on-wet to ensure that the surface is saturated.
5. Remove any excess material with a damp cloth.

Packaging

10, 25 and 1000 L

Consumption

Consumption is 1-2 m²/L, this depends on the absorbency and porosity of the surface.

Practical information

- Do not mix or dilute with other products.
- At high temperatures, strong winds or hot surfaces the product will evaporate quicker which results in a reduced penetration depth.
- Can give a slight colour deepening effect on the surface.

Storage

Can be kept for at least 12 months in original unopened packaging.

Store in a cool, frost-free place.

Health and safety

Avoid eye contact, wear safety goggles. If in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Valeton 15, 5301 LW Zaltbommel

T. +31 418 680 680

E. info@mavro-int.com

W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2020

All previous editions become invalid upon this publication

Product code: 54089