

MAVROSEAL WETLOOK

High-quality water based impregnating agent with a colour enhancing effect

Product description

Mavroseal Wetlook is a high-quality water based impregnating agent based on modified polysiloxanes with special colour enhancing components.

Mavroseal Wetlook forms a water repellent barrier after application on contact with atmospheric air without affecting the water vapor permeability of the substrate.

Mavroseal Wetlook penetrates the surface and makes it water repellent, while at the same time intensifying the colour without gloss.

Use

Mavroseal Wetlook is used to brighten dull and colorless wall and floor surfaces, stairs, entrances and terraces.

Mavroseal Wetlook is suitable for all absorbent natural or artificial stones including marble, travertine, sandstone, concrete blocks, terrazzo and granite.

Characteristics

- High and durable water resistant
- 100% vapor permeable
- High penetration ability
- Reduces dirt-adhesion
- Prevents white deposit
- Colour deepening effect (wet-look)
- Waterbased
- Consolidating effect on the surface

Technical data

Odour:	Odourless
Colour:	White
Specific weight:	1,0 kg/L
pH:	7-8
Solid content:	50%

Application conditions

Ambient temperature:	maximum 30°C, minimum 10°C
Substrate temperature:	maximum 30°C, minimum 10°C
Relative humidity:	max.95% and 3°C above dewpoint During application and drying.

Instructions

1. Clean facades with a pressure washer. For extremely polluted surfaces use a suitable façade-cleaner such as Facadeclean. Remove algae, moss and mold with Algen Remover.
2. Cover surfaces that will not be treated such as glass, window frames, pavement and plants with foil.
3. Ensure that the surface is completely dry.
4. Apply Mavroseal Wetlook undiluted with a low pressure spray or roller
5. Apply an eventual second layer wet-on-wet to ensure that the surface is saturated.
6. Remove any excess material with a damp cloth.

Drying

Water resistant:	after 6 hours
Dry:	after 24 hours

Packaging

10 L

Consumption

Consumption is 1-4 m²/L, this depends on the absorbency and porosity of the surface.

Practical information

- Do not mix or dilute with other products.
- At high temperatures, strong winds or hot surfaces the product will evaporate quicker which results in a reduced penetration depth.
- Mavroseal Wetlook is very sensitive to moisture, close packages tightly after each use!

Storage

Can be kept for at least 12 months in original unopened packaging.

Store in a cool, frost-free place.

Health and safety

Avoid skin and eye contact, wear suitable resistant gloves, protective clothing, safety goggles, and face protection. If in doubt, always consult the safety data sheet or our R&D department

Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel

T. +31 418 680 680

E. info@mavro-int.com

W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: October 2021

All previous editions become invalid upon this publication

Product code: 57645

