

# CEMENT RESIDUE REMOVER

Powerful acidic cleaner for the removal of cement residues and stubborn calcareous efflorescence.



## Product description

Cement Residue Remover is a powerful acidic cleaner based on hydrochloric acid and phosphoric acid. Cement Residue Remover effectively removes early white deposits, efflorescence and cement residue. Use Cement Residue Remover is suitable for cleaning acid resistant, mineral surfaces such as brickwork and tiles.

## Characteristics

- Quick and efficient cleaning
- Friendly on most surfaces
- Leaves no residue

## Technical data

Odour: Mildly acidic

Colour: Transparent

Specific weight: 1,20 kg/L

pH: ~1

Contains: Hydrochloric acid and phosphoric acid

## Application conditions

1. Cement Residue Remover can be used in all dry weather conditions.

## Instructions

2. Apply Cement Residue Remover undiluted with a brush. Pour the product on horizontal areas and spread with a brush or broom.
3. Let the product work on the surface for 5 – 60 minutes. Make sure to keep the surface moist.
4. Rinse the surface with a high-pressure spray. Depending on the substrate, use between 50 and 200 bar of pressure. Use cold or warm water with a maximum temperature of 50°C.
5. Repeat the procedure if necessary.

## Packaging

1, 5 and 10 L

## Consumption

Consumption is between 5-15 m<sup>2</sup>/L. Consumption highly depends on the nature and degree of pollution and the porosity of the surface.

## Practical information

- Do not mix with other products. Be especially careful with alkali products.
- Low temperatures can delay the efficacy, adjust the treatment time accordingly.
- Do not apply on hot surfaces or in direct sunlight.
- Do not allow the product to dry on the surface.
- When used indoors, ensure proper ventilation.
- Use Cement Residue Remover Gel when a longer process time is required on vertical surfaces.

## Storage

Can be kept for at least 12 months in original unopened packaging. Store in a ventilated, cool and frost-free place.

## Health and safety

Causes severe burns and eye damage. Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. If in doubt, always consult the safety data sheet or our R&D department.



## Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel  
T. +31 418 680 680  
E. [info@mavro-int.com](mailto:info@mavro-int.com)  
W. [www.mavro-int.com](http://www.mavro-int.com)

## Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: September 2020  
All previous editions become invalid upon this publication

Product code: 57655