

GRAFFITI GEL 221 RS

The most effective product for removing graffiti from trains, buses, metros and other rolling stock

Product description

Graffiti Gel 221 RS (rolling stock) is a mild, gel graffiti remover based on environmentally friendly and biodegradable solvents. Graffiti Gel 221 RS in short: Fast, effective, biodegradable, friendly to use and gentle to the original finishing material. Graffiti Gel 221 RS is the most used and recommended product by national and international public transport companies and has been tested by various authorities and universities. Graffiti Gel 221 RS has a typical mild odour and its gel consistency makes it very suitable for vertical surfaces such as the exterior of rolling stock.

Use

Graffiti Gel 221 RS has been specially developed for the removal of graffiti on the exterior of rolling stock. Virtually all of the surfaces, such as the train exterior, windows, handles and stairs can be easily treated with Graffiti Gel 221 RS.

Characteristics

- Biodegradable (OECD test 302b)
- Mild fragrance
- Suitable for indoor and outdoor use
- Quickly and effectively removes all types of graffiti
- Suitable for virtually all surfaces

Technical data

Odour:	Mild
Colour:	Yellow
Specific weight:	1,05 kg/L
pH:	~7 (neutral)
Contains:	Solvents

Application conditions

Graffiti Gel 221 RS can be used in all dry weather conditions.

Instructions

1. Prior to application place an Absorbent Roll underneath the surface that will be treated to collect any paint residues.
2. Apply Graffiti Gel 221 RS undiluted on the graffiti with a soft brush.
3. Allow the product to work 3-5 minutes and rub the graffiti with a hard or soft brush to speed up the process (agitating).
4. Allow the product to work on the surface for 10-15 minutes until the graffiti is visually dissolving.
5. Remove the dissolved graffiti from the surface with low pressure and warm water or with rubber squeegees.
6. When using rubber squeegees, neutralize the surface with a wet cloth or sponge.
7. Remove any stubborn paint residues with a plastic scraper or non-abrasive white pad.

Packaging

1 and 10 L

Consumption

Take into account a consumption of 2-7 m²/L, depending on the surface and the graffiti.

Practical information

- Do not dilute or mix with other products.



- Low temperatures can decrease the efficiency, adjust the treatment time accordingly. In temperatures lower than 8°C it is recommended to use Graffiti Gel 221 RS Winter Edition.
- Do not use in direct sunlight or warm surfaces.
- Clean tools and remove product residues with clean water.
- Please note that after removing graffiti, the surface of the rolling stock will be softer and more fragile than normal for the next 24 hours.

Storage

Can be kept for at least 12 months in original unopened packaging. Store in a cool, frost-free place.

Health and safety

Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. When in doubt, always consult the safety data sheet or our R&D department.

Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680
E. info@mavro-int.com
W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2023

All previous editions become invalid upon this publication

Product code: 57617