

GRAFFITI GEL

Powerful and easy to use cleaner for the removal of graffiti and paint

Product description

Graffiti Gel is an effective and easy to use cleaner for removing graffiti and paint from various mineral surfaces. Graffiti Gel is a gel-like product and is highly suitable for use on vertical surfaces and reduces spillage.

Use

Graffiti Gel is suitable for use on porous and hard surfaces like granite, stone, marble, limestone, slate, concrete, masonry and inorganic paints. Graffiti Gel can also be used on hard surfaces like metal, glass, treated wood, clinker, glazed tiles and some plastics.

Characteristics

- Biodegradable
- Suitable for de removal of oil-based products
- Suitable for use on many types of surfaces
- Cleans quick and effectively (even in cold conditions)
- Gel-like substance (prevents unnecessary spillage)

Technical data

Colour:	Yellow
Odour:	Characteristic
Specific weight:	1,05 kg/L
pH:	Not applicable
Contains:	1-methoxy-2-propanol, Triethanolamine

Application conditions

Graffiti Gel can be used in all dry weather conditions.

Instructions

Graffiti removal from walls, concrete and other porous surfaces:

1. Cover floors using a suitable absorbent material such as absorbent rolls.
2. Apply Graffiti Gel undiluted to the surface using a chemical resistant brush.
3. Let the product dwell on the surface for 20 to 60 minutes and regularly agitate the graffiti using a brush.
4. Jet off the graffiti using high pressure (150 bar) and hot water (90°C).
5. Optional: apply a permanent or semi-permanent anti-graffiti coating directly after removal of graffiti.
6. Remove remaining shadows/pigment using Shadow Remover

Graffiti removal from metal, glass and other hard non-porous surfaces:

1. Apply a small amount of Graffiti Gel on a dry microfiber cloth or power sponge.
2. Apply the product to the graffiti and allow to dwell for 5-15 minutes.
3. Wipe off the graffiti using a clean part of the cloth and rinse the surface with plenty clean water.

Packaging

10 L

Consumption

5 - 10 m²/L depending on the porosity of the surface and the type of graffiti.



Practical information

- Do not dilute or mix with other products.
- Low temperatures require a longer dwelling time.
- Do not use in direct sun or on hot surfaces.
- Clean tools and product residues using clean water.

Storage

Can be stored in original unopened packaging for at least 24 months. Store in a dry, cool and frost-free place.

Health and safety

Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. If in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel

T. +31 418 680 680

E. info@mavro-int.com

W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2020

All previous editions become invalid upon this publication

Product code: 57617/W