

# GRAFFITI REMO- VER GEL STRONG

Very strong alkaline hybrid remover for the most stubborn paint, graffiti, markers and shadows



## Product description

Graffiti Remover Gel Stong is an alkaline product and will bite through the most stubborn forms of graffiti, marker, shadows and paint. Graffiti Remover Gel Stong has been specially developed as a hybrid product and is therefore an ink remover, graffiti remover, paint stripper and shadow remover in one.

Graffiti Remover Gel Stong is a gel-like product and is therefore very suitable on vertical surfaces and unnecessary wastage is limited. Graffiti Remover Gel Stong is suitable for use in low temperatures due to its formulation.

## Use

Graffiti Remover Gel Stong is mainly used for the removal of graffiti on porous and hard surfaces such as masonry, facades and concrete. Graffiti Remover Gel Stong can also be used on hard surfaces like metal, glass, treated wood, clinker, glazed tiles and some plastics.

## Characteristics

- Removes the most stubborn graffiti, markers and paints quickly and effectively
- Suitable for many surfaces
- Extremely powerful dissolving power
- Very suitable for removing graffiti, ink and paint from masonry, concrete and facades
- Also suitable for removing shadows.

## Technical data

Odour:	Characteristic
Colour:	Dark brown
Specific weight:	0,99 kg/L
pH:	~ 14 ( high alkaline)
Contains:	Solvents
Flashpoint:	~ 60°C

## Application conditions

Graffiti Remover Gel Stong can be used in all dry weather conditions.

## Instructions

Graffiti removal from walls, concrete and other porous surfaces:

1. Cover floors using a suitable absorbent material such as Absorbent Rolls.
2. Apply Graffiti Remover Gel Stong undiluted to the surface using a chemical resistant brush.
3. Let the product dwell on the surface for 20 to 60 minutes and regularly agitate the graffiti using a brush.
4. Jet off the graffiti using high pressure (150 bar) and hot water (90°C). Pressure depends on the surface.

Optional: apply a permanent or semi-permanent anti-graffiti coating directly after removal of graffiti.

5. Graffiti removal from metal, glass and other hard non-porous surfaces:
6. Apply a small amount of Graffiti Remover Gel Stong on a dry microfiber cloth or power sponge.
7. Apply the product to the graffiti and allow to dwell for 5-30 minutes.

8. Wipe off the graffiti using a clean part of the cloth and rinse the surface with plenty clean water.
9. Optional: apply a permanent or semi-permanent anti-graffiti coating directly after removal of graffiti.

## Packaging

1 and 10 L

## Consumption

Take into account a consumption of 5 - 10 m<sup>2</sup>/L surfaces and 5 - 15 m<sup>2</sup>/L on non-porous surfaces. Consumption always depends on the surface and the graffiti.

## Practical information

- Do not dilute or mix with other products, be careful with acidic products.
- Low temperature can decrease the efficiency, adjust the dwelling time accordingly.
- Do not use in direct sunlight or on hot surfaces.
- Clean tools and product residues with clean water.
- Fragile surfaces might get damaged due to the powerful and active working of Graffiti Remover Gel Stong. For this reason it is highly recommended to set up a test piece beforehand, if in doubt choose one of our milder removers.

## Storage

Can be stored in original unopened packaging for at least 24 months. Store in a dry, well ventilated, cool and frost-free place.

## Health and safety

Provide adequate ventilation. Prevent release into the sewer or surrounding (ground) water. May cause severe skin and eye irritation. Avoid skin and eye contact at all times, wear suitable rubber gloves, protective clothing and safety goggles. When in doubt, always consult the safety data sheet or our R&D department.



## Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel  
 T. +31 418 680 680  
 E. [info@mavro-int.com](mailto:info@mavro-int.com)  
 W. [www.mavro-int.com](http://www.mavro-int.com)

**Disclaimer**

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: July 2020  
All previous editions become invalid upon this publication

Product code: 57697