

INK REMOVER GEL

Specially developed gel remover for removing markers, paint pens, felt pens (permanent marker) and other inks

Product description

Ink Remover Gel is a gel remover based on special solvents and surfactants designed for removing inks. Marker, felt-tip and other forms of ink are very persistent. With a strong product like the Ink Remover Gel, these inks can be removed quickly and easily. Ink Remover Gel is biodegradable.

Use

Ink Remover Gel is very suitable for use on porous and non-porous surfaces such as brickwork, concrete, siding and other mineral surfaces. Very suitable for use on vertical parts such as walls and facades where a long treatment time is desired. Ink Remover Gel is widely used on buildings, trains, subways, buses, trash cans and other street furniture.

Characteristics

- Biodegradable
- Quickly and effectively removes all types of marker, ink and shadows
- Due to the gel form it is very suitable for use on vertical surfaces.
- Suitable for many types of surfaces.
- Works quickly and effectively

Technical data

Odour:	Characteristic
Colour:	Brown
Specific weight:	0,97 kg/L
pH:	Highly alkaline
Contains:	1-butylpyrrolidin-2-one, 2-butoxyethanol, potassiumhydroxide
Flashpoint:	>90°C

Application conditions

Ink Remover Gel can be used in all dry weather conditions.

Instructions

Removing marker and ink from walls, concrete and other porous surfaces:

1. Apply Ink Remover Gel on to the surface with a chemical resistant brush.
2. Let the product work for 15 minutes up to 4 hours.
3. Rinse the surface with high pressure (depending on the surface) and hot water (approx. 90°C).

Removing marker and ink from hard, non-porous surfaces:

4. Apply Ink Remover Gel with a clean, dry microfiber cloth and apply the product on the surface.
5. Allow the product to work 5-30 minutes on the surface and wipe the graffiti with a clean part of the cloth. If necessary, support with a white pad or power sponge on very stubborn graffiti.
6. Rinse thoroughly with clean water afterwards to stop the product from working.

Packaging

1 and 5 L



Consumption

Take into account a consumption of 5-10 m²/L on porous surfaces and 5-15 m²/L on non-porous surfaces. Consumption always depends on the surface and the graffiti.

Practical information

- Do not dilute or mix with other products. Be careful with acidic products.
- Low temperature can decrease the efficiency, adjust the dwelling time accordingly.
- Do not use in direct sunlight or on hot surfaces.
- Clean tools and product residues with clean water.

Storage

Can be stored in original unopened packaging for at least 24 months. Store in a dry, cool and frost-free place.

Health and safety

May cause burns and eye damage. Highly flammable, keep away from sparks and open flames. Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. When in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680
E. info@mavro-int.com
W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: Oktober 2021
All previous editions become invalid upon this publication

Product code: 57695