

# SHADOW REMOVER GEL

Specially developed gel remover for removing graffiti shadows

## Product description

Shadow Remover Gel is a specially developed graffiti shadow remover. Shadows often remain after graffiti removal, especially on porous surfaces such as masonry and concrete.

Shadow Remover Gel penetrates deep into the pores of the substrate through the special composition to remove the last shadows.

Shadow Remover Gel is suitable for both indoor and outdoor use and is completely biodegradable according to the OECD test 302b.

Shadow Remover Gel is a gel product and is therefore very suitable for application on vertical surfaces such as walls and facades.

## Use

Shadow Remover Gel is particularly suitable for porous surfaces such as granite, natural stone, concrete, masonry, tiles, wood and limestone.

Shadow Remover Gel is also suitable for many non-porous, smooth surfaces. Always place a test piece to make sure that the substrate is not affected.

Do not use Shadow Remover Gel on soft metal surfaces such as aluminium and copper!

## Characteristics

- Effectively and quickly removes shadows
- Applicable on almost all surfaces
- Completely biodegradable
- Very suitable for application on vertical surfaces where a longer treatment time is required
- Dries slowly and therefore has a longer and more effective function.

## Technical data

Odour:	Mild
Colour:	Yellow/Orange
Specific weight:	1,085 kg/L
pH:	14 (strong alkaline)
Contains:	Potassiumhydroxide, 2-butoxyethanol

## Application conditions

Shadow Remover Gel can be used in all dry weather conditions.

## Instructions

- Apply Shadow Remover Gel undiluted to the surface with a chemical resistant brush.
- Allow the product to work on the surface for 2-30 minutes.
- Jet the shadows off with high pressure (70-150 bar) and hot water (40-90°C).
- For the removal of shadows on light porous surfaces such as plastic, Shadow Remover Gel can be applied with a power sponge to efficiency.

## Packaging

1 and 5 L

## Consumption

Consumption is between 2-5 m<sup>2</sup>/L depending on the contamination.

## Practical information

- Do not mix with other products. Be especially careful with acidic products.
- Low temperatures can delay the efficacy, adjust the treatment time accordingly.
- Do not use in direct sunlight or hot surfaces.
- Clean tools and product residues with clean water.

## Storage

Can be kept for at least 24 months in original unopened packaging.

Store in a cool and frost-free place.

## Health and safety

Can cause severe burns and permanent eye damage. Avoid skin and eye contact at all times, wear suitable gloves, protective clothing and safety goggles. In case of contact with skin or eyes, rinse immediately with plenty of water. When in doubt, always consult the safety data sheet or our R&D department.



## Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel

T. +31 418 680 680

E. [info@mavro-int.com](mailto:info@mavro-int.com)

W. [www.mavro-int.com](http://www.mavro-int.com)

## Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: January 2021

All previous editions become invalid upon this publication

Product code: 57619