

SHADOW REMOVER

Specially developed remover for removing graffiti shadows



Product description

Shadow Remover is a specially developed graffiti shadow remover. Shadows often remain after graffiti removal, especially on porous surfaces such as masonry and concrete.

Shadow Remover penetrates deep into the pores of the substrate through the special composition to remove the last shadows.

Shadow Remover is suitable for both indoor and outdoor use and is completely biodegradable according to the OECD test 302b.

Use

Shadow Remover is particularly suitable for porous surfaces such as granite, natural stone, concrete, masonry, tiles, wood and limestone.

Shadow Remover is also suitable for many non-porous, smooth surfaces. Always place a test piece to make sure that the substrate is not affected.

Do not use Shadow Remover on soft metal surfaces such as aluminum and copper!

Characteristics

- Effectively and quickly removes shadows
- Applicable on almost all surfaces
- Completely biodegradable

Technical data

Odour:	Mild
Colour:	Brown
Specific weight:	0,85 kg/L
pH:	~ 14 (strong alkaline)
Contains:	Potassium hydroxide and 2-butoxyethanol

Application conditions

Shadow Remover can be used in all dry weather conditions.

Instructions

1. Apply Shadow Remover undiluted to the surface with a chemical resistant brush.
2. Allow the product to work on the surface for 2-30 minutes.
3. Jet the shadows off with high pressure (70-150 bar) and hot water (40-90°C).
4. For the efficient removal of shadows on light porous surfaces such as plastic, Shadow Remover can be applied with a power sponge.

Packaging

1 and 10 L

Consumption

Consumption is between 2-5 m²/L depending on the contamination.

Practical information

- Do not mix with other products. Be especially careful with acidic products.
- Low temperatures can delay the efficacy, adjust the treatment time accordingly.
- Do not use in direct sunlight or hot surfaces.
- Clean tools and product residues with clean water.

Storage

Can be kept for at least 24 months in original unopened packaging.

Store in a cool and frost-free place.

Health and safety

Can be kept for at least 24 months in original unopened packaging.

Store in a cool and frost-free place.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel

T. +31 418 680 680

E. info@mavro-int.com

W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: Jan 2021

All previous editions become invalid upon this publication

Product code: 57648