

STRIP-OFF HD

Powerful paint stripper for the removal of durable 2-component coatings and multiple layers of old paint



Product description

Strip-Off HD is a powerful gel stripper based on formic acid and powerful solvents. Strip-Off HD has been specially developed for removing the most durable 2-component epoxy and polyurethane coatings and other heavy-duty paint layers. Strip-Off HD is a gel-like product which allows for good adhesion on vertical surfaces and longer dwell times.

Use

Strip-Off HD can be used on concrete, stucco, granite, masonry, wood, plastics, glass and metal. Strip-Off HD do not apply on acid-sensitive surfaces such as marble, limestone and some metals. Always test the product on the material before using.

Characteristics

- Very powerful and fast-acting
- Biodegradable
- Removes several layers of durable paint
- Strong adhesion and long open time for optimal effect
- Also effective as a glue remover

Technical data

Odour:	Sharp
Colour:	Light red
Specific weight:	1,02 kg/l
pH:	1 (acidic)
Contains:	Formic acid, 2-butoxyethanol, benzyl alcohol, γ-butyrolactone

Application conditions

Strip-Off HD can be used outdoors in all dry weather conditions.

Instructions

1. Apply Strip-Off HD undiluted with a brush or roller in a thick layer.
2. Allow the product to work for 30 minutes to 36 hours depending on the temperature and the number of layers of paint. Prevent the product from drying. For long exposure times, cover the surface with foil to prevent drying.
3. Spray the dissolved paint from the substrate with high pressure (50 - 300 bar) and hot water (70 - 90 °C). Work from the bottom up. Adjust the pressure to the substrate.
4. Scrape off the dissolved paint on sensitive surfaces with a putty knife or plastic scraper.
5. After cleaning, rinse the surface thoroughly with clean water and Uniclean Low Foaming.

Packaging

1 and 10 L

Consumption

Consumption is 0,25-2 m²/L, depending on the type of surface and amount of paint layers.

Practical information

- Do not dilute or mix with other products. Be careful with alkaline products.
- Collect paint and product residues with Absorbent Rolls.
- For the removal of highly chemical resistant coatings/paints or for extra fast stripping, roughen the surface with sandpaper before applying product.
- Low temperatures can delay the effectiveness, adjust the dwell time accordingly.
- Do not apply in direct sunlight or on hot surfaces.

Storage

Can be kept for at least 24 months in original unopened packaging.
Store in a well-ventilated, cool and frost-free place.

Health and safety

Avoid inhalation of aerosols, vapor and mist, provide adequate ventilation. Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. In case of inadequate ventilation wear a suitable ABEK filter. When in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680
E. info@mavro-int.com
W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: January 2021

All previous editions become invalid upon this publication

Product code: 57647