

STRIP-OFF PLUS

Very fast and effective stripper for all types of coatings and paints



Product description

Strip-Off Plus is a powerful stripper for the removal of several layers of paint in one treatment. Strip-Off Plus is gel-like and therefore adheres well to almost all surfaces. Strip-Off Plus contains only biodegradable solvents and is free from NMP and methylene chloride.

Use

Strip-Off Plus is universally applicable and removes quickly and effectively alkyd, acrylic, latex, polyurethane, epoxy and 2-component coatings. Strip-Off Plus can be used safely on almost all types of metal, mineral and wooden substrates. Examples are concrete, stucco, granite, limestone, sandstone, masonry, glass and metal. Can damage some plastics, always make a test piece beforehand.

Characteristics

- and therefore friendly to most surfaces
- Works also at low temperatures
- Does not contain methylene chloride, NMP, NEP, acids or alkalis
- Quickly removes multiple layers of paint
- Strong adhesion and long open time for optimal effect
- Easy to use

Technical data

Odour:	Characteristic
Colour:	Greyish
Specific weight:	1,0 kg/L
pH:	not applicable
Flashpoint:	23°C
VOC-content:	943 g/l

Application conditions

Strip-Off Plus can be used in all dry weather conditions.

Instructions

1. Apply Strip-Off Plus undiluted with a brush or roller in a thick layer.
2. Allow the product to work in for 30 minutes to 1 hour, depending on the temperature and the number of coats. Avoid that the product dries out, cover with plastic if necessary.
3. Spray the dissolved paint from the substrate with high pressure (50 - 300 bar) and hot water (70 - 90°C). Work from the bottom up. Adjust the pressure to the substrate.
4. On sensitive surfaces, scrape away the dissolved paint with a spatula or plastic scraper.
5. After cleaning, rinse the substrate thoroughly with clean water.

Packaging

1 and 10 kg

Consumption

Consumption is 0,25 - 1 m² per kg, depending on the surface and number of paint layers.

Practical information

- Do not dilute or mix with other products.
- Low temperatures can slow down the effect, so adjust the application time accordingly.
- Do not apply on hot surfaces or in direct sunlight.
- Collect paint and product residues with Absorbent Rolls.

Storage

In original unopened containers shelf life of at least 12 months. Store in a well-ventilated cool place away from ignition sources.

Health and safety

Avoid inhalation, ensure adequate ventilation and wear respiratory protection with brown filter. Avoid skin and eye contact, wear suitable solvent resistant gloves, protective clothing and safety glasses or face shield. If in doubt, always consult the safety data sheet or our R&D department.



Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel
T. +31 418 680 680
E. info@mavro-int.com
W. www.mavro-int.com

Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: May 2021
All previous editions become invalid upon this publication

Product code: 57633