

# TAR REMOVER

Powerful remover for removing heavy tar build-up and old Tectyl® residue pollution.

## Product description

Tar Remover is a powerful product for the removal of extremely greasy pollution such as tar, old Tectyl® residue and hydraulic oil. Tar Remover is a highly concentrated mixture of powerful surfactants that dissolves even the most stubborn tar build-up. Tar Remover is safe for the user, friendly to the environment and completely biodegradable.

## Use

Tar Remover can be safely applied on almost all porous and non-porous surfaces such as metal, powder coatings, plastics, concrete, masonry and natural stone. The product is gentle on the surface and can be used safely on sensitive surfaces such as reflectors and traffic signs.

Tar Remover is particularly suitable for removing tar from rolling stock, trucks, cars and other vehicles.

Tar Remover is widely used for cleaning (pipe) lines, couplings and surfaces in the construction and (petro) chemical industry.

## Characteristics

- Quickly and effectively removes tar, old Tectyl® residue, wax, oil and other greasy and oil-based contaminants.
- Safe and gentle on almost all surfaces
- Strong resolving power
- Completely biodegradable
- Can be used both indoors and outdoors

## Technical data

Odour:	Odourless
Colour:	Transparent
Specific weight:	0,87 kg/L
pH:	9,5
Contains:	Alcohols, C9-C11, Ethoxylated, Fatty alcohol ethoxylated

## Application conditions

Tar Remover can be used in all dry weather conditions.

## Instructions

### Large surfaces

1. Apply Tar Remover undiluted with a low pressure sprayer, brush or broom.
2. Let the product act for 10 minutes to several hours. Regularly agitating with a scouring pad, broom or brush accelerates the product.
3. Spray the dissolved contamination from the substrate with appropriate pressure and hot water (70-80°C)

### Loose parts

4. Immerse loose parts with stubborn tar in a bucket or bath with Tar Remover.
5. Leave the part on for up to 24 hours and then rinse with hot water.

## Packaging

5 L



## Consumption

Take into account a consumption of 5 - 10 m<sup>2</sup>/L. Consumption always depends on the surface and the degree of pollution.

## Practical information

- Do not dilute or mix with other products.
- Low temperature can decrease the efficiency, adjust the dwelling time accordingly.
- Clean tools and product residues with clean water.

## Storage

Can be stored in original unopened packaging for at least 24 months. Store in a dry, cool and frost-free place.

## Health and safety

Avoid skin and eye contact, wear suitable gloves, protective clothing and safety goggles. When in doubt, always consult the safety data sheet or our R&D department.



## Technical support

Mavro is ISO 9001 certified: your guarantee of quality, in terms of products and advice. Our technical consultants and R&D department are always at your service. We are happy to look at your problem or wish with you. Help you with our products or find a solution if it does not yet exist. Call, e-mail or drop by.

Mavro International, Heksekamp 1, 5301 LX Zaltbommel

T. +31 418 680 680

E. [info@mavro-int.com](mailto:info@mavro-int.com)

W. [www.mavro-int.com](http://www.mavro-int.com)

## Disclaimer

This technical data sheet is intended as a guide for the use of the product and is based on the latest development and technology. Because application, processing and environmental conditions are out of our reach, no rights can be derived from this technical data sheet. Mavro International rejects all liability regarding warranty, incorrect application and any damage or consequential damage. The user remains responsible at all times regarding proper use, product choice, application and results.

Edition: March 2021

All previous editions become invalid upon this publication

Product code: 57667