

## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name **Ceradur® Metal**  
Alternative number(s) 58002

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Coating for particular industrial and professional uses

#### 1.3 Details of the supplier of the safety data sheet

Mavro International BV  
Heksekamp 1  
5301 LX Zaltbommel  
Netherlands

Telephone: +31 418 680 680  
e-mail: [info@mavro-int.com](mailto:info@mavro-int.com)  
Website: <https://www.mavro-int.com>

#### 1.4 Emergency telephone number

Emergency information service +31 418 680 680  
This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

| Poison centre  |  |                  |               |         |                               |
|----------------|--|------------------|---------------|---------|-------------------------------|
| Country        | Name   | Postal code/city | Telephone     | Telefax | Opening hours                 |
| United Kingdom | National Poisons Information Service (Birmingham Centre) City Hospital |                  | 0344 892 0111 |         | Mon - Fri 12:00 AM - 12:00 AM |

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification acc. to GHS

| Section | Hazard class              | Category | Hazard class and category | Hazard statement |
|---------|---------------------------|----------|---------------------------|------------------|
| 2.6     | flammable liquid          | 2        | Flam. Liq. 2              | H225             |
| 3.10    | acute toxicity (oral)     | 4        | Acute Tox. 4              | H302             |
| 3.2     | skin corrosion/irritation | 1        | Skin Corr. 1              | H314             |
| 3.4S    | skin sensitisation        | 1        | Skin Sens. 1              | H317             |

## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

| Section | Hazard class  | Category | Hazard class and category | Hazard statement |
|---------|---|----------|---------------------------|------------------|
| 3.8D    | specific target organ toxicity – single exposure (narcotic effects, drowsiness) | 3        | STOT SE 3                 | H336             |
| 4.1C    | hazardous to the aquatic environment – chronic hazard                           | 3        | Aquatic Chronic 3         | H412             |

For full text of abbreviations: see SECTION 16.

### The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

## 2.2 Label elements

### Labelling

- Signal word            danger

- Pictograms

GHS02, GHS05,  
GHS07



- Hazard statements

H225                    Highly flammable liquid and vapour.  
H302                    Harmful if swallowed.  
H314                    Causes severe skin burns and eye damage.  
H317                    May cause an allergic skin reaction.  
H336                    May cause drowsiness or dizziness.  
H412                    Harmful to aquatic life with long lasting effects.

- Precautionary statements

P210                    Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260                    Do not breathe dust/fume/gas/mist/vapours/spray.  
P280                    Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353    IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P305+P351+P338    IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310                    Immediately call a POISON CENTER/doctor.  
P370+P378            In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.  
P403+P233            Store in a well-ventilated place. Keep container tightly closed.  
P403+P235            Store in a well-ventilated place. Keep cool.

- Hazardous ingredients for labelling

Organic polysilazane compound, n-butyl acetate, 3-aminopropyltriethoxysilane

## 2.3 Other hazards

### Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0,1\%$ .

### Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

## CERADUR® METAL

 Version number: GHS 2.0  
 Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27





### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not relevant (mixture)

#### 3.2 Mixtures

Description of the mixture

| Name of substance             | Identifier   | Wt%       | Classification acc. to GHS   | Pictograms  |
|-------------------------------|--|-----------|--|---|
| Organic polysilazane compound | CAS No<br>475645-84-2  | 50 – < 75 | Flam. Liq. 2 / H225<br>Acute Tox. 4 / H302<br>Skin Corr. 1 / H314<br>Aquatic Chronic 3 / H412                                |    |
| n-butyl acetate               | CAS No<br>123-86-4<br><br>EC No<br>204-658-1<br><br>Index No<br>607-025-00-1 | 25 – < 50 | Flam. Liq. 3 / H226<br>STOT SE 3 / H336  |    |
| 3-aminopropyltriethoxysilane  | CAS No<br>919-30-2<br><br>EC No<br>213-048-4<br><br>Index No<br>612-108-00-0 | 10 – < 25 | Acute Tox. 4 / H302<br>Skin Corr. 1B / H314  |  |
| toluene                       | CAS No<br>108-88-3<br><br>EC No<br>203-625-9<br><br>Index No<br>601-021-00-3 | < 1       | Flam. Liq. 2 / H225<br>Skin Irrit. 2 / H315<br>Repr. 2 / H361d<br>STOT SE 3 / H336<br>STOT RE 2 / H373<br>Asp. Tox. 1 / H304 |  |

| Name of substance            | Specific Conc. Limits | M-Factors | ATE         | Exposure route |
|------------------------------|-----------------------|-----------|-------------|----------------|
| 3-aminopropyltriethoxysilane | -                     | -         | 1,780 mg/kg | oral           |

For full text of abbreviations: see SECTION 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice.

##### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

##### Following skin contact

Wash with plenty of soap and water.

## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

**Following eye contact**

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

**Following ingestion**

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

**4.2 Most important symptoms and effects, both acute and delayed**

Narcotic effects.

**4.3 Indication of any immediate medical attention and special treatment needed**

none

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media**

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

**Unsuitable extinguishing media**

Water jet

**5.2 Special hazards arising from the substance or mixture**

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

**Hazardous combustion products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Remove persons to safety.

**For emergency responders**

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

**6.2 Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

**6.3 Methods and material for containment and cleaning up****Advice on how to contain a spill**

Covering of drains

**Advice on how to clean up a spill**

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

### Appropriate containment techniques

Use of adsorbent materials.

### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

## 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Recommendations

#### - Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

#### - Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feed-stuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

#### - Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

#### - Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

#### - Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

#### - Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

| Occupational exposure limit values (Workplace Exposure Limits) |                 |          |            |           |                          |            |                           |                 |                                |          |              |
|--|-----------------|----------|------------|-----------|--------------------------|------------|---------------------------|-----------------|--------------------------------|----------|--------------|
| Country  | Name of agent   | CAS No   | Identifier | TWA [ppm] | TWA [mg/m <sup>3</sup> ] | STEL [ppm] | STEL [mg/m <sup>3</sup> ] | Ceiling-C [ppm] | Ceiling-C [mg/m <sup>3</sup> ] | Notation | Source       |
| EU   | toluene         | 108-88-3 | IOELV      | 50        | 192                      | 100        | 384                       |                 |                                | H        | 2006/15/EC   |
| EU   | n-butyl acetate | 123-86-4 | IOELV      | 50        | 241                      | 150        | 723                       |                 |                                |          | 2019/1831/EU |
| GB   | toluene         | 108-88-3 | WEL        | 50        | 191                      | 100        | 384                       |                 |                                |          | EH40/2005    |
| GB   | butyl acetate   | 123-86-4 | WEL        | 150       | 724                      | 200        | 966                       |                 |                                |          | EH40/2005    |

#### Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

H absorbed through the skin

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

| Relevant DNELs of components of the mixture |          |          |                       |                                    |                   |                            |
|---|----------|----------|-----------------------|------------------------------------|-------------------|----------------------------|
| Name of substance                           | CAS No   | Endpoint | Threshold level       | Protection goal, route of exposure | Used in           | Exposure time              |
| 3-aminopropyltriethoxysilane                | 919-30-2 | DNEL     | 59 mg/m <sup>3</sup>  | human, inhalatory                  | worker (industry) | chronic - systemic effects |
| 3-aminopropyltriethoxysilane                | 919-30-2 | DNEL     | 59 mg/m <sup>3</sup>  | human, inhalatory                  | worker (industry) | acute - systemic effects   |
| 3-aminopropyltriethoxysilane                | 919-30-2 | DNEL     | 8.3 mg/kg bw/day      | human, dermal                      | worker (industry) | chronic - systemic effects |
| 3-aminopropyltriethoxysilane                | 919-30-2 | DNEL     | 8.3 mg/kg bw/day      | human, dermal                      | worker (industry) | acute - systemic effects   |
| toluene                                     | 108-88-3 | DNEL     | 192 mg/m <sup>3</sup> | human, inhalatory                  | worker (industry) | chronic - systemic effects |
| toluene                                     | 108-88-3 | DNEL     | 384 mg/m <sup>3</sup> | human, inhalatory                  | worker (industry) | acute - systemic effects   |
| toluene                                     | 108-88-3 | DNEL     | 192 mg/m <sup>3</sup> | human, inhalatory                  | worker (industry) | chronic - local effects    |
| toluene                                     | 108-88-3 | DNEL     | 384 mg/m <sup>3</sup> | human, inhalatory                  | worker (industry) | acute - local effects      |
| toluene                                     | 108-88-3 | DNEL     | 384 mg/kg bw/day      | human, dermal                      | worker (industry) | chronic - systemic effects |

## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

| Relevant PNECs of components of the mixture |          |          |                 |                       |                              |                              |
|---|----------|----------|-----------------|-----------------------|------------------------------|------------------------------|
| Name of substance                           | CAS No   | Endpoint | Threshold level | Organism              | Environmental compartment    | Exposure time                |
| 3-aminopropyltriethoxysilane                | 919-30-2 | PNEC     | 0.33 mg/l       | aquatic organisms     | freshwater                   | short-term (single instance) |
| 3-aminopropyltriethoxysilane                | 919-30-2 | PNEC     | 0.033 mg/l      | aquatic organisms     | marine water                 | short-term (single instance) |
| 3-aminopropyltriethoxysilane                | 919-30-2 | PNEC     | 13 mg/l         | aquatic organisms     | sewage treatment plant (STP) | short-term (single instance) |
| 3-aminopropyltriethoxysilane                | 919-30-2 | PNEC     | 1.2 mg/kg       | aquatic organisms     | freshwater sediment          | short-term (single instance) |
| 3-aminopropyltriethoxysilane                | 919-30-2 | PNEC     | 0.12 mg/kg      | aquatic organisms     | marine sediment              | short-term (single instance) |
| 3-aminopropyltriethoxysilane                | 919-30-2 | PNEC     | 0.05 mg/kg      | terrestrial organisms | soil                         | short-term (single instance) |
| toluene                                     | 108-88-3 | PNEC     | 0.68 mg/l       | aquatic organisms     | freshwater                   | short-term (single instance) |
| toluene                                     | 108-88-3 | PNEC     | 0.68 mg/l       | aquatic organisms     | marine water                 | short-term (single instance) |
| toluene                                     | 108-88-3 | PNEC     | 13.61 mg/l      | aquatic organisms     | sewage treatment plant (STP) | short-term (single instance) |
| toluene                                     | 108-88-3 | PNEC     | 16.39 mg/kg     | aquatic organisms     | freshwater sediment          | short-term (single instance) |
| toluene                                     | 108-88-3 | PNEC     | 16.39 mg/kg     | aquatic organisms     | marine sediment              | short-term (single instance) |
| toluene                                     | 108-88-3 | PNEC     | 2.89 mg/kg      | terrestrial organisms | soil                         | short-term (single instance) |

## 8.2 Exposure controls

### Appropriate engineering controls

General ventilation.

### Individual protection measures (personal protective equipment)

#### Eye/face protection

Wear eye/face protection.

#### Skin protection

##### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374.

##### - Type of material

Nitrile

##### - Material thickness

>0,12mm

##### - Breakthrough times of the glove material

>480 minutes (permeation: level 6)

##### - Other protection measures

Wash hands thoroughly after handling.

## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

### Body protection

Protective clothing against liquid chemicals.

### Respiratory protection

Type: ABEK-P2 (combined filters against gases, vapours and particles, colour code: Brown/Grey/Yellow/Green/White).

### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|  |  |
|--|--|
| Physical state   | liquid   |
| Colour   | colourless                                       |
| Odour  | like ammonia                                     |
| Melting point/freezing point                             | not determined                                   |
| Boiling point or initial boiling point and boiling range | 126.2 °C at 1,013 hPa                            |
| Flammability   | flammable liquid in accordance with GHS criteria |
| Lower and upper explosion limit                          | not determined                                   |
| Flash point  | 16 °C at 1,013 hPa                               |
| Auto-ignition temperature                                | 435 °C   |
| Decomposition temperature                                | not relevant                                     |
| pH (value)   | not determined                                   |
| Kinematic viscosity                                      | not determined                                   |
| Solubility(ies)  | not determined                                   |

### Partition coefficient

|   |                                   |
|---|-----------------------------------|
| Partition coefficient n-octanol/water (log value) | this information is not available |
|---|-----------------------------------|

|                 |                |
|-----------------|----------------|
| Vapour pressure | not determined |
|-----------------|----------------|



**CERADUR® METAL**

 Version number: GHS 2.0  
 Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

**Density and/or relative density**

|                         |   |
|-------------------------|---|
| Density                 | 0.92 g/cm <sup>3</sup>                        |
| Relative vapour density | information on this property is not available |

|                          |                       |
|--------------------------|-----------------------|
| Particle characteristics | not relevant (liquid) |
|--------------------------|-----------------------|

**9.2 Other information**

|  |                                    |
|--|------------------------------------|
| Information with regard to physical hazard classes | there is no additional information |
| Other safety characteristics                       | there is no additional information |

**SECTION 10: Stability and reactivity**
**10.1 Reactivity**

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

**10.2 Chemical stability**

See below "Conditions to avoid".

**10.3 Possibility of hazardous reactions**

No known hazardous reactions.

**10.4 Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Hints to prevent fire or explosion**

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

**10.5 Incompatible materials**

Oxidisers

**10.6 Hazardous decomposition products**

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

**CERADUR® METAL**

 Version number: GHS 2.0  
 Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

**SECTION 11: Toxicological information**
**11.1 Information on toxicological effects**

Test data are not available for the complete mixture.

**Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

**Classification acc. to GHS**
**Acute toxicity**

Harmful if swallowed.

| Acute toxicity estimate (ATE) of components of the mixture |          |                |             |
|--|----------|----------------|-------------|
| Name of substance  | CAS No   | Exposure route | ATE         |
| 3-aminopropyltriethoxysilane                               | 919-30-2 | oral           | 1,780 mg/kg |

**Skin corrosion/irritation**

Causes severe skin burns and eye damage.

**Serious eye damage/eye irritation**

Causes serious eye damage.

**Respiratory or skin sensitisation**

May cause an allergic skin reaction.

**Germ cell mutagenicity**

Shall not be classified as germ cell mutagenic.

**Carcinogenicity**

Shall not be classified as carcinogenic.

**Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

**Specific target organ toxicity - single exposure**

May cause drowsiness or dizziness.

**Specific target organ toxicity - repeated exposure**

Shall not be classified as a specific target organ toxicant (repeated exposure).

**Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

**11.2 Information on other hazards**

There is no additional information.

## CERADUR® METAL

 Version number: GHS 2.0  
 Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

### SECTION 12: Ecological information

#### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

| Aquatic toxicity (chronic) of components of the mixture |          |          |           |                       |               |
|---|----------|----------|-----------|-----------------------|---------------|
| Name of substance                                       | CAS No   | Endpoint | Value     | Species               | Exposure time |
| n-butyl acetate   | 123-86-4 | EC50     | 34.2 mg/l | aquatic invertebrates | 21 d          |
| n-butyl acetate   | 123-86-4 | LC50     | 43.5 mg/l | aquatic invertebrates | 21 d          |
| 3-aminopropyltriethoxysilane                            | 919-30-2 | EC50     | 43 mg/l   | microorganisms        | 5.75 h        |
| toluene   | 108-88-3 | LC50     | 3.78 mg/l | aquatic invertebrates | 2 d           |
| toluene   | 108-88-3 | EC50     | 3.23 mg/l | aquatic invertebrates | 7 d           |

#### 12.2 Persistence and degradability

| Degradability of components of the mixture |          |                  |                  |      |        |        |
|--|----------|------------------|------------------|------|--------|--------|
| Name of substance                          | CAS No   | Process          | Degradation rate | Time | Method | Source |
| n-butyl acetate                            | 123-86-4 | oxygen depletion | 80 %             | 5 d  |        | ECHA   |
| 3-aminopropyltriethoxysilane               | 919-30-2 | DOC removal      | 67 %             | 28 d |        | ECHA   |

#### 12.3 Bioaccumulative potential

Data are not available.

| Bioaccumulative potential of components of the mixture |          |     |                           |          |
|--|----------|-----|---------------------------|----------|
| Name of substance                                      | CAS No   | BCF | Log KOW                   | BOD5/COD |
| n-butyl acetate  | 123-86-4 |     | 2.3 (pH value: ~7, 25 °C) |          |
| 3-aminopropyltriethoxysilane                           | 919-30-2 | 3.4 | 1.7 (pH value: 7, 20 °C)  |          |
| toluene  | 108-88-3 | 90  | 2.73 (pH value: 7, 20 °C) |          |

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

 According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0,1\%$ .

#### 12.6 Endocrine disrupting properties

 Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

#### 12.7 Other adverse effects

Data are not available.

## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Waste treatment-relevant information

Solvent reclamation/regeneration.

##### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

##### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

##### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

|           |         |
|-----------|---------|
| ADR/RID   | UN 2924 |
| IMDG-Code | UN 2924 |
| ICAO-TI   | UN 2924 |

#### 14.2 UN proper shipping name

|  |                                       |
|--|---------------------------------------|
| ADR/RID                                | FLAMMABLE LIQUID, CORROSIVE, N.O.S.   |
| IMDG-Code                              | FLAMMABLE LIQUID, CORROSIVE, N.O.S.   |
| ICAO-TI                                | Flammable liquid, corrosive, n.o.s.   |
| Technical name (hazardous ingredients) | toluene, 3-aminopropyltriethoxysilane |

#### 14.3 Transport hazard class(es)

|           |       |
|-----------|-------|
| ADR/RID   | 3 (8) |
| IMDG-Code | 3 (8) |
| ICAO-TI   | 3 (8) |

#### 14.4 Packing group

|           |    |
|-----------|----|
| ADR/RID   | II |
| IMDG-Code | II |
| ICAO-TI   | II |

#### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

#### 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

#### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)


Revision: 2023-06-27

### Information for each of the UN Model Regulations

#### Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) - Additional information

|   |     |
|---|-----|
| Classification code   | FC  |
| Danger label(s)   | 3+8 |
|  |     |
| Special provisions (SP)   | 274 |
| Excepted quantities (EQ)  | E2  |
| Limited quantities (LQ)   | 1 L |
| Transport category (TC)   | 2   |
| Tunnel restriction code (TRC)   | D/E |
| Hazard identification No  | 338 |
| Emergency Action Code   | 3WE |

#### Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) - Additional information

|   |     |
|---|-----|
| Classification code   | FC  |
| Danger label(s)   | 3+8 |
|  |     |
| Special provisions (SP)   | 274 |
| Excepted quantities (EQ)  | E2  |
| Limited quantities (LQ)   | 1 L |
| Transport category (TC)   | 2   |
| Hazard identification No  | 338 |

#### International Maritime Dangerous Goods Code (IMDG) - Additional information

|   |          |
|---|----------|
| Marine pollutant  | -        |
| Danger label(s)   | 3+8      |
|  |          |
| Special provisions (SP)   | 274      |
| Excepted quantities (EQ)  | E2       |
| Limited quantities (LQ)   | 1 L      |
| EmS   | F-E, S-C |
| Stowage category  | B        |

## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 3+8



Special provisions (SP) A3

Excepted quantities (EQ) E2

Limited quantities (LQ) 0,5 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

#### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

#### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

| Pollutant release and transfer registers (PRTR) |          |         |   |
|---|----------|---------|---|
| Name of substance                               | CAS No   | Remarks | Threshold for releases to air (kg/year) |
| toluene   | 108-88-3 | (11)    |   |

#### Legend

(11) Single pollutants are to be reported if the threshold for BTEX (the sum parameter of benzene, toluene, ethyl benzene, xylenes) is exceeded

#### Water Framework Directive (WFD)

| List of pollutants (WFD) |        |           |         |
|--------------------------|--------|-----------|---------|
| Name of substance        | CAS No | Listed in | Remarks |
| toluene                  |        | a)        |         |

#### Legend

A) Indicative list of the main pollutants

#### Regulation on persistent organic pollutants (POP)

None of the ingredients are listed.

#### National inventories

| Country | Inventory  | Status                         |
|---------|------------|--------------------------------|
| EU      | REACH Reg. | not all ingredients are listed |

#### Legend

REACH Reg. REACH registered substances

### 15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

### SECTION 16: Other information

#### Abbreviations and acronyms

| Abbr.           | Descriptions of used abbreviations   |
|-----------------|--|
| 2006/15/EC      | Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC |
| 2019/1831/EU    | Commission Directive establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC                |
| Acute Tox.      | Acute toxicity   |
| ADR             | Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)                                      |
| Aquatic Chronic | Hazardous to the aquatic environment - chronic hazard  |
| Asp. Tox.       | Aspiration hazard  |
| ATE             | Acute Toxicity Estimate  |
| BCF             | Bioconcentration factor  |
| BOD             | Biochemical Oxygen Demand  |
| CAS             | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)   |
| Ceiling-C       | Ceiling value  |
| COD             | Chemical oxygen demand   |
| DGR             | Dangerous Goods Regulations (see IATA/DGR)   |
| DNEL            | Derived No-Effect Level  |
| EC50            | Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval                   |
| EC No           | The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)                  |
| EH40/2005       | EH40/2005 Workplace exposure limits ( <a href="http://www.nationalarchives.gov.uk/doc/open-government-licence/">http://www.nationalarchives.gov.uk/doc/open-government-licence/</a> )              |
| EINECS          | European Inventory of Existing Commercial Chemical Substances  |
| ELINCS          | European List of Notified Chemical Substances  |
| EmS             | Emergency Schedule   |
| Flam. Liq.      | Flammable liquid   |
| GHS             | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations  |
| IATA            | International Air Transport Association  |
| IATA/DGR        | Dangerous Goods Regulations (DGR) for the air transport (IATA)   |
| ICAO            | International Civil Aviation Organization  |
| ICAO-TI         | Technical instructions for the safe transport of dangerous goods by air  |
| IMDG            | International Maritime Dangerous Goods Code  |
| IMDG-Code       | International Maritime Dangerous Goods Code  |

## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

| Abbr.       | Descriptions of used abbreviations  |
|-------------|---|
| index No    | The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008  |
| IOELV       | Indicative occupational exposure limit value  |
| LC50        | Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval                       |
| log KOW     | n-Octanol/water   |
| NLP         | No-Longer Polymer   |
| PBT         | Persistent, Bioaccumulative and Toxic   |
| PNEC        | Predicted No-Effect Concentration   |
| ppm         | Parts per million   |
| REACH       | Registration, Evaluation, Authorisation and Restriction of Chemicals  |
| Repr.       | Reproductive toxicity   |
| RID         | Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail) |
| Skin Corr.  | Corrosive to skin   |
| Skin Irrit. | Irritant to skin  |
| STEL        | Short-term exposure limit   |
| STOT RE     | Specific target organ toxicity - repeated exposure  |
| STOT SE     | Specific target organ toxicity - single exposure  |
| TWA         | Time-weighted average   |
| vPvB        | Very Persistent and very Bioaccumulative  |
| WEL         | Workplace exposure limit  |

### Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text  |
|------|---|
| H225 | Highly flammable liquid and vapour.           |
| H226 | Flammable liquid and vapour.                  |
| H302 | Harmful if swallowed.                         |
| H304 | May be fatal if swallowed and enters airways. |
| H314 | Causes severe skin burns and eye damage.      |



## CERADUR® METAL

Version number: GHS 2.0  
Replaces version of: 2023-04-19 (GHS 1)

Revision: 2023-06-27

| Code  | Text   |
|-------|--|
| H315  | Causes skin irritation.  |
| H317  | May cause an allergic skin reaction.                               |
| H336  | May cause drowsiness or dizziness.                                 |
| H361d | Suspected of damaging the unborn child.                            |
| H373  | May cause damage to organs through prolonged or repeated exposure. |
| H412  | Harmful to aquatic life with long lasting effects.                 |

**Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.